

TECHNICAL DATA SHEET | INTERIOR & EXTERIOR

RMC TANNIN PRIMER

Preparation

Rubio Monocoat Tannin Primer is a preventive treatment for untreated tannic wood, suitable for internal and external (sheltered) use.

Rubio Monocoat Tannin Primer prevents and delays the appearance of surface tannin marks. This product is ideal for use on parquet flooring, furniture, worktops and external woodwork, in combination with Rubio Monocoat finishing oils. Rubio Monocoat Tannin Primer is resinand polymer-free, as a result of which the optimal molecular bonding of the Rubio Monocoat oils with the wood remains guaranteed.



PRODUCT INFORMATION

> Technical characteristics

- · Physical state (20°C): liquid
- · Look/colour: opaque
- Odour: odourless
- Density (20°C) (ASTM D 4052): 1,01 kg/L
- · Solubility: soluble in water

> Packaging

Bottle 100ml and 1L, jerrycan 5L

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Do not allow to freeze.

APPLICATION INFORMATION

> Instructions

- STEP 1. Sand the surface without making scratches until all residues of previous treatments are removed and remove all dust residue thoroughly.
- STEP 2. Apply Rubio Monocoat Tannin Primer using a brush, roller or spray at a rate of 50 g/m². Even out with a cloth in the direction of the boards to prevent puddles.
- STEP 3. Allow to dry thoroughly.
- STEP 4. Remove any raised fibres using a beige Rubio Monocoat Pad.
- STEP 5. Wipe down the surface and apply your choice of Rubio Monocoat finishing oil.

> Tips

- · Effective on Oak, Chestnut, Red Cedar and Teak.
- · Ideal for removing the pinkish appearance of oils, particularly for invisible and white effects.
- Never use on wood that received a reactive treatment.
- · Can lighten old oak parquet flooring, stairs, doors, furniture etc. and restore its former beauty with Rubio Monocoat Oil Plus 2C.

> Coverage

Approx. 50 g/m²

These usages are merely indicative. Results depend on wood type, wear and tear and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.



TECHNICAL DATA SHEET | INTERIOR & EXTERIOR

> Tools





> Related products





Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit **www.rubiomonocoat.com**

YOUR DISTRIBUTOR:

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 14/06/2019. Check the safety information before using the product.**





MUYLLE 1 FACON

Muylle Facon BVBA Ambachtenstraat 58 8870 Izegem (BELGIË)

Tel. +32 (0) 51 30 80 54 Fax +32 (0) 51 30 99 78 info@muyllefacon.be

www.rubiomonocoat.com