

Rubiemonocoat GREASE REMOVER

DESCRIPTION:

Rubio Monocoat Grease Remover is a ready-to-use product that removes recent grease stains from a surface treated with Rubio Monocoat Oil. The product should be applied immediately after the stain occurs thereby preventing the grease from penetrating the surface.

APPLICATION:

1. Spray RMC Grease Remover on the stain.
2. Allow several minutes for absorption.
3. Dab dry using a cloth or paper towel.
4. Rinse the whole surface thoroughly using a damp cloth, or clean the surface using RMC Surface Care.

For stubborn marks, it is recommended to repeat this method as many times as needed to achieve the desired result.

TECHNICAL CHARACTERISTICS:

Consistency: liquid

Colour: clear, blue

Flash point: ca. 11 °C

Density (20 °C) (ASTM D 4052): 0.806 – 0.850 kg/L

Solubility in water: fully

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging.
Do not allow to freeze.

PACKAGING:

Ecospray 0,5 L

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.

Consult the safety sheet before use.
Date TDS: 14/04/14

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax +32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiemonocoat.com

